

Non-sparking Embedment Sensors - Self Certified



ATEX
II 3 G Ex nA IIC u



Overview

- Non-sparking embedment sensors for monitoring the temperature of thrust bearings
- Four case styles offer a variety of installation options
- Certified for use in Zone 2, Group IIC hazardous areas

Specifications

Temperature range: -50 to 200°C (-58 to 392°F), reducing to 125°C (257°F) when elastomer filled cable is ordered.

Case: Tin plated copper alloy.

Babbitt tip: Factory applied babbitt tip, available on case style A, B, and short style B, reduces the danger of overheating the sensor when installed in babbitt layer.

Leads:

RTD: stranded copper with PTFE insulation.

Stainless steel braid, FEP over PTFE and FEP over stainless steel braid with elastomer fill are optional.

Thermocouple: stranded, PTFE insulated, twisted pairs.

Stainless steel braid, FEP over PTFE and FEP over stainless steel braid with elastomer fill are optional.

Leadwire size (AWG):

RTD					
Case style	Number of leads				
	2	3	4	6	8
A	24	24	24	24	
B	24	24	28	28	28
C	24	26	30	30	
Short B	24	26	28	30	
Thermocouple					
All cases	24		24		

Time constant: 3.0 seconds (case style A), typical in moving water.

Insulation resistance: 10 megohms minimum at 100 VDC, leads to case.

▼ = **STANDARD OPTIONS**

Specifications subject to change





Specification and order options:





RTD

S102617PD	Model number from next page
3	Number of leads per sensing element (2, 3 or 4): CA or PD elements not available with 2 leads 4 leads available on all single elements and dual S102618 and S102662 only
F	Covering over leadwires: T = PTFE insulated leads only S = Stainless steel overbraid with PTFE insulated leads F = FEP over PTFE insulated leads E = FEP over stainless steel braid with elastomer fill and PTFE Insulated leads (max. fill length 240")
48	Lead length in inches
(Stop here for case style C or D; no installation variable)	
B0	Optional Installation/Accessory option: B0 = No babbitt metal or accessories B1 = Babbitt metal applied AC1 = Supplied with AC171 spring and AC172 series ring (case style B only) AC2 = Supplied with AC171 spring and AC1038 ring (case style B only) AC3 = Supplied with AC171 spring and AC915-1 ring (case style B only)
S102617PD3F48B0 = Sample part number	

Thermocouple

TC102621E	Model number from next page
U	Junction grounding: G = Grounded U = Ungrounded
48	Lead length in inches
F	Covering over leadwires: T = PTFE insulated leads only S = Stainless steel overbraid with PTFE insulated leads F = FEP over PTFE insulated leads E = FEP over stainless steel braid with elastomer fill and PTFE Insulated leads (max. fill length 240")
(Stop here for case style C or D; no installation variable)	
B0	Optional Installation/Accessory option: B0 = No babbitt metal or accessories B1 = Babbitt metal applied AC1 = Supplied with AC171 spring and AC172 series ring (case style B only) AC2 = Supplied with AC171 spring and AC1038 ring (case style B only) AC3 = Supplied with AC171 spring and AC915-1 ring (case style B only)
TC102621EU48FB0 = Sample part number	

RTD Element	TCR $\Omega/\Omega/^{\circ}\text{C}$	Case style A Case L: 0.250" (6.4 mm) Case \varnothing : 0.275" (7.0 mm) 		Case style B Case L: 0.250" (6.4 mm) Case \varnothing : 0.188" (4.8 mm) Flange \varnothing : 0.250" (6.4 mm) 		Case style C Case L: 0.300" (7.6 mm) Case \varnothing : 0.125" (3.2 mm) 		Short case style B Case L: .188" (4.8 mm) Case \varnothing : .188" (4.8 mm) Flange \varnothing : 0.250" (6.4 mm) 	
		Single	Dual	Single	Dual	Single	Dual	Single	Dual
Platinum, 100 Ω \pm 0.36% at 0°C	.00392	S102617PA	S102617PAPA	S102618PA	S102618PAPA	S102619PA	S102619PAPA	S102662PA	S102662PAPA
Platinum, 100 Ω \pm 0.12% at 0°C (Meets EN60751, Class B)	.00385	S102617PD	S102617PDPD	S102618PD	S102618PDPD	S102619PD	S102619PDPD	S102662PD	S102662PDPD
Platinum, 100 Ω \pm 0.36% at 0°C	.00385	S102617PE	S102617PEPE	S102618PE	S102618PEPE	S102619PE	S102619PEPE	S102662PE	S102662PEPE
Platinum, 1000 Ω \pm 0.12% at 0°C	.00385	S102617PF	S102617PFPF	S102618PF	S102618PFPF	S102619PF	S102619PFPF	S102662PF	S102662PFPF
Copper, 10 Ω \pm 0.2% at 25°C	.00427	S102617CA	S102617CACA	S102618CA		S102619CA		S102662CA	
Nickel, 120 Ω \pm 0.5% at 0°C	.00672	S102617NA	S102617NANA	S102618NA	S102618NANA	S102619NA		S102662NA	S102662NANA

Thermocouple Junction Type	Case style A Case L: 0.250" (6.4 mm) Case \varnothing : 0.275" (7.0 mm) 		Case style B Case L: 0.250" (6.4 mm) Case \varnothing : 0.188" (4.8 mm) Flange \varnothing : 0.250" (6.4 mm) 		Case style C Case L: 0.300" (7.6 mm) Case \varnothing : 0.125" (3.2 mm) 		Short case style B Case L: .188" (4.8 mm) Case \varnothing : .188" (4.8 mm) Flange \varnothing : 0.250" (6.4 mm) 	
	Single	Dual	Single	Dual	Single	Dual	Single	Dual
E = Chromel-Constantan	TC102620E	TC102620EE	TC102621E	TC102621EE	TC102622E	TC102622EE	TC102663E	TC102663EE
J = Iron-Constantan	TC102620J	TC102620JJ	TC102621J	TC102621JJ	TC102622J	TC102622JJ	TC102663J	TC102663JJ
K = Chromel-Alumel	TC102620K	TC102620KK	TC102621K	TC102621KK	TC102622K	TC102622KK	TC102663K	TC102663KK
T = Copper-Constantan	TC102620T	TC102620TT	TC102621T	TC102621TT	TC102622T	TC102622TT	TC102663T	TC102663TT

STOP OIL SEEPAGE!

Feedthroughs provide an oil tight seal where a cable exits a machine housing. The stainless steel tube is epoxy filled and each wire is sealed to the individual conductor. This prevents wicking of oil inside the wires as well as leakage around the wire insulation. Pressure rating to 25 psi (1.7 bar.) See page 3-11 for details.

Leadwire and cable seal models FG1015, FG3015 and FG4015 seal RTD or thermocouple leadwires where they exit oil-filled bearing housings of rotating equipment. Both versions include a grommet that provides the seal and allows adjustment of the wire or cable position. See page 3-12 for details.

Elastomer rubber-filled cable has elastomer fill between the wires, stainless steel braid, and outer jacket. This fill can extend along the entire length of the cable, or a specified portion. The outside of the cable can be sealed with an FG1015, FG3015 and FG4015 fitting. See Leadwire Covering Options on Miniature Sensors on pages 6-2 to 6-10.


Minco Application Aid #27 provides more information on the problems of oil seepage and various solutions. Download AA#27 at www.minco.com



▼ = STANDARD OPTIONS
Specifications subject to change

Non-sparking Embedment Sensors

ATEX  **II 3 G Ex nA IIC Gc**
IECEx Ex nA IIC Gc



Overview

- Non-sparking embedment sensors for monitoring the temperature of thrust bearings
- Four case styles offer a variety of installation options
- Certified for use in Zone 2, Group IIC hazardous areas, defined by EN/IEC 60079-0 and EN/IEC 60079-15

Specifications

Temperature range: -50 to 200°C (-58 to 392°F), reducing to 125°C (257°F) when elastomer filled cable is ordered.

Case: Tin plated copper alloy.

Babbitt tip: Factory applied babbitt tip, available on case style A, B, and short style B, reduces the danger of overheating the sensor when installed in babbitt layer.

Leads:

RTD: stranded copper with PTFE insulation.

Stainless steel braid, FEP over PTFE and FEP over stainless steel braid with elastomer fill are optional.

Thermocouple: stranded, PTFE insulated, twisted pairs.

Stainless steel braid, FEP over PTFE and FEP over stainless steel braid with elastomer fill are optional.

Leadwire size (AWG):

RTD					
Case style	Number of leads				
	2	3	4	6	8
A	24	24	24	24	
B	24	24	28	28	28
C	24	26	30	30	
Short B	24	24	28	28	
Thermocouple					
All cases	24		24		

Time constant: 3.0 seconds (case style A), typical in moving water.

Insulation resistance: 10 megohms minimum at 100 VDC, leads to case.

▼ = **STANDARD OPTIONS**
 Specifications subject to change

Specification and order options:

RTD

S207596PD	Model number from next page
3	Number of leads per sensing element (2, 3 or 4): CA or PD elements not available with 2 leads 4 leads available on all single elements and dual S207596 + S207598 only
E	Covering over leadwires: T = PTFE insulated leads only S = Stainless steel overbraid with PTFE insulated leads F = FEP over PTFE insulated leads E = FEP over stainless steel braid, with elastomer fill and PTFE insulated leads (max. fill length 240")
40	Lead length in inches ▼:40, 120
(Stop here for case style C; no installation variable)	
AC1	Optional Installation/Accessory option B0 = No babbitt metal or accessories B1 = Babbitt metal applied AC1 = Supplied with AC171 spring and AC172 series ring (case style B only) AC2 = Supplied with AC171 spring and AC1038 ring (case style B only) AC3 = Supplied with AC171 spring and AC915-1 ring (case style B only)
S207596PD3E40AC1 = Sample part number	

Thermocouple

TC207600K	Model number from next page
U	Junction grounding: G = Grounded U = Ungrounded
40	Lead length in inches ▼:40, 120
S	Covering over leadwires: T = PTFE insulated leads only S = Stainless steel overbraid with PTFE insulated leads F = FEP over PTFE insulated leads E = FEP over stainless steel braid, with elastomer fill and PTFE insulated leads (max fill length 240")
(Stop here for case style C; no installation variable)	
B0	Optional Installation/Accessory option B0 = No babbitt metal or accessories B1 = Babbitt metal applied AC1 = Supplied with AC171 spring and AC172 series ring (case style B only) AC2 = Supplied with AC171 spring and AC1038 ring (case style B only) AC3 = Supplied with AC171 spring and AC915-1 ring (case style B only)
TC207600KU40SB0 = Sample part number	

RTD Element	TCR $\Omega/\Omega/^{\circ}\text{C}$	Case style A Case L: 0.250" (6.4 mm) Case Ø: 0.275" (7.0 mm)		Case style B Case L: 0.250" (6.4 mm) Case Ø: 0.188" (4.8 mm) Flange Ø: 0.250" (6.4 mm)		Case style C Case L: 0.300" (7.6 mm) Case Ø: 0.125" (3.2 mm)		Short case style B Case L: .188" (4.8 mm) Case Ø: .188" (4.8 mm) Flange Ø: 0.250" (6.4 mm)	
		Single	Dual	Single	Dual	Single	Dual	Single	Dual
Platinum, 100 Ω $\pm 0.36\%$ at 0°C	.00392	S207595PA	S207595PAPA	S207596PA	S207596PAPA	S207597PA	S207597PAPA	S207598PA	S207598PAPA
Platinum, 100 Ω $\pm 0.12\%$ at 0°C (Meets EN60751, Class B)	.00385	S207595PD	S207595PDPD	S207596PD	S207596PDPD	S207597PD	S207597PDPD	S207598PD	S207598PDPD
Platinum, 100 Ω $\pm 0.067\%$ at 0°C (Meets EN60751, Class A)	.00385	S207595PM	S207595PMPM	S207596PM	S207596PMPM	S207597PM	S207597PMPM	S207598PM	S207598PMPM
Platinum, 100 Ω $\pm 0.36\%$ at 0°C	.00385	S207595PE	S207595PEPE	S207596PE	S207596PEPE	S207597PE	S207597PEPE	S207598PE	S207598PEPE
Platinum, 1000 Ω $\pm 0.12\%$ at 0°C	.00385	S207595PF	S207595PFPF	S207596PF	S207596PFPF	S207597PF	S207597PFPF	S207598PF	S207598PFPF
Copper, 10 Ω $\pm 0.2\%$ at 25°C	.00427	S207595CA	S207595CACA	S207596CA		S207597CA		S207598CA	
Nickel, 120 Ω $\pm 0.5\%$ at 0°C	.00672	S207595NA	S207595NANA	S207596NA	S207596NANA	S207597NA		S207598NA	S207598NANA

Thermocouple Junction Type	Case style A Case L: 0.250" (6.4 mm) Case Ø: 0.275" (7.0 mm)		Case style B Case L: 0.250" (6.4 mm) Case Ø: 0.188" (4.8 mm) Flange Ø: 0.250" (6.4 mm)		Case style C Case L: 0.300" (7.6 mm) Case Ø: 0.125" (3.2 mm)		Short case style B Case L: .188" (4.8 mm) Case Ø: .188" (4.8 mm) Flange Ø: 0.250" (6.4 mm)	
	Single	Dual	Single	Dual	Single	Dual	Single	Dual
E = Chromel-Constantan	TC207600E	TC207600EE	TC207601E	TC207601EE	TC207602E	TC207602EE	TC207603E	TC207603EE
J = Iron-Constantan	TC207600J	TC207600JJ	TC207601J	TC207601JJ	TC207602J	TC207602JJ	TC207603J	TC207603JJ
K = Chromel-Alumel	TC207600K	TC207600KK	TC207601K	TC207601KK	TC207602K	TC207602KK	TC207603K	TC207603KK
T = Copper-Constantan	TC207600T	TC207600TT	TC207601T	TC207601TT	TC207602T	TC207602TT	TC207603T	TC207603TT

STOP OIL SEEPAGE!

Feedthroughs provide an oil tight seal where a cable exits a machine housing. The stainless steel tube is epoxy filled and each wire is sealed to the individual conductor. This prevents wicking of oil inside the wires as well as leakage around the wire insulation. Pressure rating to 25 psi (1.7 bar.) See page 3-11 for details.

Leadwire and cable seal models FG1015, FG3015 and FG4015 seal RTD or thermocouple leadwires where they exit oil-filled bearing housings of rotating equipment. Both versions include a grommet that provides the seal and allows adjustment of the wire or cable position. See page 3-12 for details.

Elastomer rubber-filled cable has elastomer fill between the wires, stainless steel braid, and outer jacket. This fill can extend along the entire length of the cable, or a specified portion. The outside of the cable can be sealed with an FG1015, FG3015 and FG4015 fitting. See Leadwire Covering Options on Miniature Sensors on pages 6-2 to 6-10.



Minco Application Aid #27 provides more information on the problems of oil seepage and various solutions. Download AA#27 at www.minco.com

▼ = STANDARD OPTIONS
Specifications subject to change