

Intrinsically Safe Portable Ruggedized Test Gauges

- ❑ Class I, Division 1, Groups A, B, C, D
- ❑ All Metal Housing
- ❑ Digi-Max® with Min/Max, Zero
- ❑ ±0.25% Accuracy, 316L SS Sensor

- Battery Powered Test Gauges
- Natural Gas Pipeline Pressures
- Aircraft Tire Pressure
- NEC Hazardous Areas

Agency Approval

Factory Mutual Approved
Intrinsically Safe for Class I, Division 1,
Groups, A, B, C, D Hazardous Locations

Info Quick Link
cecomp.com/is



Ranges and Resolution

See range table for ranges and engineering units.
Standard: Range, resolution, and units are factory set
D4: Selectable engineering units

Display

Standard: 3.5 digit LCD, 0.5" H
D4: 4 digit LCD, 0.5" H, 0.25" H alphanumeric lower
BL: Red LED display backlight
3 readings per second update rate

Accuracy

Standard: ±0.25% of full scale ±1 least significant digit
Optional: HA ±0.1% FS ±1 LSD (most ranges)

Batteries

Two AAA alkaline

Housing

Aluminum case and bezel
3.38" W x 2.88" H x 1.65" D
Add approximately 0.75" to height for pressure fitting

Connection and Material

¼" NPT male fitting
316L SS wetted parts

Environmental

Standard operating temp.: -40 to 185°F (-40 to 85°C)
D4 operating temperature: -4 to 185°F (-20 to 85°C)
Compensated temperature: 32 to 158°F (0 to 70°C)



DPG2000B with RB Rubber Boot



DPG2000B _-D4 with RB Rubber Boot



DPG2000B _-D4-Mx with RB Rubber Boot



Aircraft Tire Pressure



Honeywell TFE Jet Engine Testing



Natural Gas Distribution Pressure Test Kits



Industrial Gauge Manifold



Aircraft Strut Check

To Order				
Model Series	Range	Display-Memory	Auto Shutoff Time	Options

Model	Ranges	Keypad	Display	Backlight	Bat. Hrs.	Calibration	Units	Memory	Auto Shutoff
DPG2000B	Vacuum to 1999 psi, gauge, absolute, bipolar	1 button on/off	3.5 digit LCD, 0.5" H.	none	1000	Top zero and span pots.	Factory set	none	-5 5 min. factory set
DPG2000BBL				Hold button	150-1000				-10 10 min. factory set
DPG2000B _-D4	Vacuum to 5000 psi, gauge, absolute, compound, bipolar	1 button on/off/zero	4 digit LCD, 0.5" H and 5 character display	none	1000	Internal buttons, lockout switch, zero, span, linearity	Internal button select	Min/max	Internal button select for minutes, hours, or on/off
DPG2000BBL _-D4				1 minute	150-750				
DPG2000B _-D4-M1	Vacuum to 5000 psi, gauge, absolute, compound, bipolar	3 button on/off, zero/clear, memory ▼, ▲	4 digit LCD, 0.5" H and 5 character display	none	1000	Keypad zero button, pass code protected calibration via keypad internal lockout switch, zero, span, linearity	Keypad select	M1 continuous max rdg.	Keypad select for minutes, hours, or on/off
DPG2000BBL _-D4-M1				1 minute	150-750				
DPG2000B _-D4-M2				none	1000				
DPG2000BBL _-D4-M2				1 minute	150-750				
DPG2000B _-D4-M4				none	1000				
DPG2000BBL _-D4-M4				1 minute	150-750				
DPG2000B _-D4-M6				none	1000				
DPG2000BBL _-D4-M6				1 minute	150-750				
DPG2000B _-D4-M8	none	1000							
DPG2000BBL _-D4-M8	1 minute	150-750							

Ranges

Most engineering units are shown below. See price list or consult factory for additional or custom engineering units.

InHg/psig	Range Code	PSI
-29.9 inHg-15 psi	-30V15PSIG	-14.7-15.0
-29.9 inHg-100 psi	-30V100PSIG	-14.7-100
-29.9 inHg-200 psi	-30V200PSIG	-14.7-200
Pounds/sq. inch	Range Code	PSI
0-3 psi	3PSIG	3.0
0-5 psi	5PSIG	5.0
15-0 psia	15PSIA	15.0 abs
0-14.7 psi vac	15PSIGVAC	-14.7
-14.7-15.0 psi	±15PSIG	-14.7-15.0
0-15 psi	15PSIG	15.0
30-0 psia	30PSIA	30.0 abs
0-30 psi	30PSIG	30.0
0-60 psi	60PSIG	60.0
100-0 psia	100PSIA	100 abs
-14.7-100 psi	-15V100PSIG	-14.7-100
0-100 psi	100PSIG	100
-14.7-200 psi	-15V200PSIG	-14.7-200
0-200 psi	200PSIG	200
0-300 psi	300PSIG	300
0-500 psi	500PSIG	500
0-1000 psi	1000PSIG	1000
0-2000 psi	2000PSIG	2000
0-3000 psi	3000PSIG	3000
0-5000 psi	5000PSIG	5000
inches Hg (0°C)	Range Code	PSI
0-6 inHg	6INHGG	3.0
0-10 inHg	10INHGG	4.9
30-0 inHg abs	30INHGA	14.7 abs
0-29.9 inHg vac	30INHGVAC	-14.7
-29.9-30.0 inHg	±30INHGG	±14.7
0-30 inHg	30INHGG	14.7
60-0 inHg abs	60INHGA	29.5 abs
0-60 inHg	60INHGG	29.5
0-120 inHg	120INHGG	58.9
200-0 inHg abs	200INHGA	98.2 abs
0-200 inHg	200INHGG	98.2
-29.9-200 inHg	-30V200INHGG	-14.7-98.2
0-400 inHg	400INHGG	196
-29.9-400 inHg	-30V400INHGG	-14.7-196
0-600 inHg	600INHGG	295
0-1000 inHg	1000INHGG	491
Inches H ₂ O (20°C)	Range Code	PSI
0-85 inH ₂ O	85INH2OG	3.1
0-140 inH ₂ O	140INH2OG	5.1
400-0 inH ₂ O abs	400INH2OA	14.5 abs
0-408 inH ₂ O vac	400INH2OVAC	-14.7
±408 inH ₂ O	±400INH2OG	±14.7
0-400 inH ₂ O	400INH2OG	14.5
850-0 inH ₂ O abs	850INH2OA	30.7 abs
0-850 inH ₂ O	850INH2OG	30.7
Feet H ₂ O (20°C)	Range Code	PSI
0-7 ftH ₂ O	7FTH2O	3.0
0-12 ftH ₂ O	12FTH2O	5.2
0-35 ftH ₂ O	35FTH2O	15.2
0-70 ftH ₂ O	70FTH2O	30.3
0-140 ftH ₂ O	140FTH2O	60.7
0-230 ftH ₂ O	230FTH2O	99.7
0-480 ftH ₂ O	480FTH2O	208
0-700 ftH ₂ O	700FTH2O	303
0-1150 ftH ₂ O	1150FTH2O	498
0-2300 ftH ₂ O	2300FTH2O	995
0-4600 ftH ₂ O	4600FTH2O	1991
0-6900 ftH ₂ O	6900FTH2O	2986
Ounces/sq. inch	Range Code	PSI
0-50 oz/in ²	50ZING	3.1
0-80 oz/in ²	80ZING	5.0
240-0 oz/in ² abs	240ZINA	15.0 abs
0-235 oz/in ² vac	240ZINVAC	-14.7
-235-240 oz/in ²	±240ZING	-14.7-15.0
0-240 oz/in ²	240ZING	15.0
0-480 oz/in ² abs	480ZINA	30.0 abs
0-480 oz/in ²	480ZING	30.0
mm H ₂ O (20°C)	Range Code	PSI
0-2100 mmH ₂ O	2100MMH2OG	3.0
0-3500 mmH ₂ O	3500MMH2OG	5.0

3.5 digit display indicates up to 19.99, 199.9, or 1999. Some ranges may require models with 4 digit display.

cm H ₂ O (20°C)	Range Code	PSI
0-200 cmH ₂ O	200CMH2OG	2.8
0-210 cmH ₂ O	210CMH2OG	3.0
0-350 cmH ₂ O	350CMH2OG	5.0
1000-0 cmH ₂ O abs	1000CMH2OA	14.2 abs
0-1000 cmH ₂ O vac	1000CMH2OVAC	14.2 vac
±1000 cmH ₂ O	±1000CMH2OG	±14.2
0-1000 cmH ₂ O	1000CMH2OG	14.2
0-2000 cmH ₂ O	2000CMH2OG	28.4
0-2100 cmH ₂ O	2100CMH2OG	29.9
kiloPascals	Range Code	PSI
0-20 kPa	20KPAG	2.9
0-35 kPa	35KPAG	5.1
100-0 kPa abs	100KPAA	14.5 abs
0-101 kPa vac	100KPAVAC	-14.7
-101-100 kPa	±100KPAG	-14.7-14.5
0-100 kPa	100KPAG	14.5
200-0 kPa abs	200KPAA	29.0 abs
0-200 kPa	200KPAG	29.0
0-400 kPa	400KPAG	58
700-0 kPa abs	700KPAA	102 abs
-101-700 kPa	-100V700KPAG	-14.7-102
0-700 kPa	700KPAG	102
-101-1400 kPa	-100V1400KPAG	-14.7-203
0-1400 kPa	1400KPAG	203
0-2000 kPa	2000KPAG	290
0-3500 kPa	3500KPAG	508
0-7000 kPa	7000KPAG	1015
MegaPascal	Range Code	PSI
-0.1-1.4 MPa	-0.1V1.4MPAG	-14.7-203
0-1.4 MPa	1.4MPAG	203
0-2 MPa	2MPAG	290
0-3.5 MPa	3.5MPAG	508
0-7 MPa	7MPAG	1015
0-14 MPa	14MPAG	2031
0-20 MPa	20MPAG	2901
0-35 MPa	35MPAG	5076
Millibar	Range Code	PSI
0-200 mbar	200MBARG	2.9
0-350 mbar	350MBARG	5.1
1000-0 mbar abs	1000MBARA	14.5 abs
0-1013 mbar vac	1000MBARVAC	-14.7
-1013-1000 mbar	±1000MBARG	-14.7-14.5
0-1000 mbar	1000MBARG	14.5
2000-0 mbar abs	2000MBARA	29.0 abs
0-2000 mbar	2000MBARG	29.0
0-4000 mbar	4000MBARG	58.0
Bar	Range Code	PSI
1-0 bar abs	1BARA	14.5 abs
1.01 bar vac	1BARVAC	-14.7
-1.01-1 bar	±1BARG	-14.7-14.5
0-1 bar	1BARG	14.5
2-0 bar abs	2BARA	29.0 abs
0-2 bar	2BARG	29.0
0-4 bar	4BARG	58.0
7-0 bar abs	7BARA	102 abs
-1.01-7 bar	-1V7BARG	-14.7-102
0-7 bar	7BARG	102
-1.01-14 bar	-1V14BARG	-14.7-203
0-14 bar	14BARG	203
0-20 bar	20BARG	290
0-35 bar	35BARG	508
0-70 bar	70BARG	1015
0-140 bar	140BARG	2031
0-200 bar	200BARG	2901
0-350 bar	350BARG	5076
grams/cm ²	Range Code	PSI
0-200 g/cm ²	200GCMG	2.8
0-350 g/cm ²	350GCMG	5.0
1000-0 g/cm ² abs	1000GCMA	14.2 abs
0-1037 g/cm ² vac	1000GCMVAC	-14.7
0-1000 g/cm ²	1000GCMG	14.2
2000-0 g/cm ² abs	2000GCMA	28.4 abs
0-2000 g/cm ²	2000GCMG	28.4
2100-0 g/cm ² abs	2100GCMA	29.9 abs
0-2100 g/cm ²	2100GCMG	29.9

Minus sign optional for vacuum models. 15 psig, 100 psig, 200 psig, and absolute sensors are for vacuum service.

kilograms/cm ²	Range Code	PSI
1-0 kg/cm ² abs	1KGCMGA	14.2 abs
0-1.03 kg/cm ² vac	1KGCMGVAC	-14.7
-1.03-1 kg/cm ²	±1KGCMG	-14.7-14.2
0-1 kg/cm ²	1KGCMG	14.2
2-0 kg/cm ² abs	2KGCMGA	28.4 abs
0-2 kg/cm ²	2KGCMG	28.4
0-4 kg/cm ²	4KGCMG	56.9
7-0 kg/cm ² abs	7KGCMGA	99.6 abs
-1.03-7 kg/cm ²	-1V7KGCMG	-14.2-99.6
0-7 kg/cm ²	7KGCMG	99.6
-1.03-14 kg/cm ²	-1V14KGCMG	-14.2-199
0-14 kg/cm ²	14KGCMG	199
0-20 kg/cm ²	20KGCMG	284
0-35 kg/cm ²	35KGCMG	498
0-70 kg/cm ²	70KGCMG	996
0-140 kg/cm ²	140KGCMG	1991
0-200 kg/cm ²	200KGCMG	2845
0-350 kg/cm ²	350KGCMG	4978
mmHg (0°C)	Range Code	PSI
0-150 mmHg	150MMHGG	2.9
0-260 mmHg	260MMHGG	5.0
760-0 mmHg abs	760MMHGA	14.7 abs
0-760 mmHg vac	760MMHGVAC	-14.7
±760 mmHg	±760MMHGG	±14.7
0-760 mmHg	760MMHGG	14.7
1600-0 mmHg	1600MMHGA	30.9 abs
0-1600 mmHg	1600MMHGG	30.9
Torr (0°C)	Range Code	PSI
760-0 Torr	760TORRA	14.7 abs
1600-0 Torr	1600TORRA	30.9 abs
Atmospheres	Range Code	PSI
1-0 atm abs	1ATMA	14.7 abs
0-1 atm vac	1ATMVAC	-14.7
±1 atm	±1ATMG	±14.7
0-1 atm	1ATMG	14.7
0-2 atm abs	2ATMA	29.4 abs
0-2 atm	2ATMG	29.4
0-4 atm	4ATMG	58.8
-1-7 atm	-1V7ATMG	-14.7-103
0-7 atm	7ATMG	103
-1-14 atm	-1V14ATMG	-14.7-206
0-14 atm	14ATMG	206
0-20 atm	20ATMG	294
0-34 atm	34ATMG	500
0-70 atm	70ATMG	1029
0-135 atm	135ATMG	1984
0-200 atm	200ATMG	2939
0-340 atm	340ATMG	4997



RB Rubber Boot



-TP Top Port Option

