

### Overview

The 5100-02-IT Combustible Gas Sensor Module is a key member of the powerful Sierra Monitor IT Series family of gas sensor modules. The 5100-02-IT provides the features needed by safety and instrumentation engineers including:

- 180 day calibration interval
- FM and UL Approval for performance & safety
- SIL-2 certified
- Modbus RTU RS-485 interface
- 4-20 mA output isolated and non-isolated
- HART Interface option
- SMC Sentry digital bus interface
- ATEX Certified
- Optional Integral and Trouble alarm relays - Alarm, Warning
- Aluminum or 316 Stainless Steel enclosure
- Non-intrusive calibration
- Integral scrolling LED display
- Optional remote sensor
- Remote alarm reset capable



Model 5100-02-IT utilizes the proven, reliable, catalytic bead technology to monitor for combustible gases (methane and others). Output range is 0-100% of Lower Explosive Limit (LEL). This detector has minimal maintenance requirements and is Factory Mutual approved for six month calibration intervals. Internal, continuous self-diagnostics automatically detect and alarm any fault problems. The 5100-02-IT can be used as a 4-20 mA component or as a Modbus RTU node. For higher level system capability the module can interface directly to Sierra Monitor's Sentry Controller enabling system level Modbus serial communications, area and zone alarm management, extensive system diagnostic features, WebServer interface, and multiplexing sensor connections.

Factory Mutual (FM) and UL 2075 Approval for performance, electrical safety and environmental parameters including Class I, Div. 1, Groups B, C, D and Class I, Zone 1, Group IIB + H<sub>2</sub> – T5. With a NEMA-4X enclosure standard, approved multiplexing, and approved six month calibration interval, cost of ownership is minimized at the acquisition, installation and operating stages.

### How It Works

Catalytic Bead gas sensors detect gas by comparing the resistance of two heated elements. One element is catalytic to enhance the burning of combustible gases, the other element is passive. Electronic circuits are used to compare the change in the catalytic bead resistance relative to the passive bead. The relative change is calibrated to determine the concentration of the gas of interest.

#### Features

- Six-month calibration interval
- Non-intrusive calibration
- Network-compatible with Modbus, 4-20 mA, Sentry bus, HART and relay interface
- FM and UL Approved for Performance and Hazardous Areas
- SIL-2 Certified
- Local scrolling display

#### Benefits

- Longest rated and FM-approved calibration cycle for any catalytic-bead gas detector - reduced maintenance
- Able to calibrate module without declassifying the area
- Easily meets user's needs for access to critical plant safety information
- Proven and approved for installation in areas where combustible gases are located
- Meets long term reliability design standards
- Ease of calibration and easy access to gas concentration, relay status and diagnostics

**Sensor****Type:** Catalytic Bead**Performance****Repeatability:** +/-1% LEL**Response Time:** T60<10sec**Calibration freq:** 180 days**Accuracy:** +/- 1% for 0-50% LEL range  
+/- 2% for 51-100% LEL range**Output****Display:** Fixed and Scrolling LED**Signal Output:** Sentry digital bus

Analog 4-20 mA

3-wire Non-Isolated

4-wire Isolated

Serial RS-485 Modbus RTU

**Relay:** Optional**Options****Relays:** 5 amp Alarm, Warning (0.25 amp Trouble)

5A@ 250 VAC, 5A@ 30VDC (Alarm, Warning)

Board includes auxiliary connection for Sentry multiplexing

**HART:** Termination board includes HART, Modbus RS-485, 4-20mA, Digital Input, 2A Relay output, No Sentry Bus**Remote Sensor:** Up to 50 feet (15.2m)**Power****Power consumption:** 3 watts maximum**Input voltage:** 24 VDC nominal: 10-30VDC**RFI/EMI Protection:** EN50081-2, EN50082-2**Operating Range****Ambient Temp Range:** -40° to 176°F (-40° to 80°C)**Relative Humidity:** 0-99% Non-Condensing**Construction****Dimensions:** (HxWxD)

(A1 &amp; A2) = 6.9 x 5.7 x 3.9 in .

(17.5 x 14.5 x 9.9 cm )

(S1 &amp; S2) = 7.5 x 5.0 x 4.4 in .

(19 x 13 x 11 cm )

**Weight:** (A1 & A2) = 3.4 lb. (1.5 Kg )

(S1 &amp; S2) = 7.2 lb. (3.3 Kg )

**Housing:** Epoxy coated Aluminum or  
316 Stainless Steel**Enclosure Hazardous Area Classification**

Explosion proof, Class I, Div. 1, Groups B, C, D

Class I, Zone 1, Group IIC, IP66, IP65, NEMA 4X

II2 GD, Ex d IIC T6 = -40°C to 85°C

**Warranty:** 2 years**Approvals****UL 2075:** Combustible Gas Detector Performance**FM Approval 6320:** Combustible Gas Detector  
Performance**FM Approval 3600:** Class I Div. 1, Groups B, C, D**SIL-2 Certified:** IEC 61508**ATEX Certified:** II 2G, Ex d IIB + H2 T5 Gb**CE Marked:** Certificate of Approval**CSA:** For enclosure in hazardous locations**ABS:** Certificate of Compliance**CQST:** Certificate for China**CCOE/PESO:** Certificate for India

\*Specifications subject to change without notice

**Remote Sensor Option**

It is often necessary to sample the combustible gas at some distance from the gas sensor module. The IT Series enables the user to mount the sensor remotely from the transmitter without the need for expensive and high-maintenance sample pumps. The Remote Sensor Option provides a separate gas sensor that can be mounted up to 50 feet from the transmitter and connected via a cable included.

**Ordering Information:** The following part number is essential in selection of the correct product. Please build up the desired part by inserting the code for each element into the appropriate space (ie. 5100-02-IT-S1-00-1-0-C).

Model	Enclosure	Relay/Connection Output	Gas Type	Sensor Protection	Remote Option	Approvals
5100-02-IT			-00			
	↓ - A1 = AL ¾" NPT - A2 = AL M20 x 1.5 - S1 = SS ¾" NPT - S2 = SS M20 x 1.5	↓ - 01 = No Relays (std) - 02 = Relays Option - 05 = HART Option		↓ - 0 = Standard	↓ - 0 = None - 1 = Remote Sensor	↓ - C = ATEX

**Accessories:**

5311-00 Rainshield  
 5311-02 Rainshield with calibration port

**Calibration Accessories:**

5358-01 Calibration Head, Standard  
 5360-00 Calibration Gas Delivery Fitting

**Calibrators High Capacity:**

1250-01 Gas Sensor Calibration Kit, Type A (CO, H2S)  
 1260-02 50% LEL Methane Gas Cylinder Type A  
 1260-30 25% LEL Methane  
 1260-42 Hydrogen, 50% LEL, Gas Cylinder, Type A  
 1260-00 Zero Gas (Air), Gas Cylinder, Type A  
 (if satisfactory zero ambient air not available)